

Product type designation

**PROFIBUS bus terminal 12M**

12M BUS TERMINAL FOR PROFIBUS, TRANSMISSION RATE 9.6 KBIT/S TO 12 MBIT/S, CONNECTING CABLE 1.5 M



**Electrical data**

Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
-------------------------------	--------------------------

**Interfaces**

Number of electrical connections	2
<ul style="list-style-type: none"> <li>• for PROFIBUS cables</li> </ul>	
Type of electrical connection	Screw terminals
<ul style="list-style-type: none"> <li>• for PROFIBUS cables</li> </ul>	

**Mechanical data**

Material / of the enclosure	plastic
-----------------------------	---------

**Design, dimensions and weight**

Width	50 mm
Height	138 mm
Depth	53 mm
Net weight	360 g
Mounting type	Yes
<ul style="list-style-type: none"> <li>• 35 mm DIN rail mounting</li> </ul>	

## Standards, specifications, approvals

### Certificate of suitability

- UL approval

Yes

## Further Information / Internet Links

### Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

**last modified:**

06/05/2017